

9	Dairy/Gaushalas	Green/ Orange	200	500	500	200	100	-	-	100	-	Distance is measured from the outer edge of cow sheds.
10	Hot Mix Plant	Orange	-	-	-	-	-	-	-	-	In general stake height should vary with the design of hot mix plant (between 10 to 25 m as may be prescribed by SPCB/CPCB).	<p>1) Approved habitation, tourist places, Schools, hospitals, sports centers etc- 1 to 2 m depending upon local condition. 2) Sensitive areas, national monuments and bird sanctuaries- 2 to 5 m depending upon buffer zone and available green belt.</p> <p>In case of existing hot mix plants not meeting above siting criteria, the unit should provide minimum 6 m high compound wall of GI sheets along plot periphery.</p>
11	DG Set	1MVA < Orange 5MVA < Red	1) Installation of DG sets may be permitted keeping eye on ambience of the locality. 2) If use of DG Sets is required over the ambience of the locality, second layer canopy/ noise barrier may be imposed to meet the ambience of the locality. 3) Necessary precaution may be taken to avoid increase in noise and vibration due to running of DG Sets. 4) 'National Committee on Noise Pollution Control' fix the limit at 25 dB(A) insertion loss or sound Pressure level (SPL) of 80 dB(A) at 1 m distance, whichever is less.									
12	Sand Mining	Green	Mining shall not be taken under in a mining lease located within 500 m of bridge, 200 m upstream and downstream of water supply scheme, 200 m from the edge of National Highway and railway line, 100 m from a reservoir canal/ irrigation scheme or building, 50 m from the edge of state highway, and 30 m from the edge of other roads.									

